

Pixo Line Driver Multipower 600 White

Code article 0007865

SYLVANIA


PROTM



Pixo Line is a linear track system, adds flexibility to any space due the variety of product options Offers an easy installation with two separate modules Push-in/push-out mechanism with GR6d-15 connector Compatible with Zhaga Book 14 Constant current 350mA -1050mA LED in-track driver with GR6d-15 connector for LED light modules, polycarbonate body Clip holder and fixing screw included in the driver box, white finishing colour, max. system power: 56W, operating voltage: 220-240V / 50-60Hz Multipower driver module with 8 power settings meet all installation needs with one single product selection and setting on driver - between 17W (350mA), 19W (400mA), 24W (500mA), 29W (600mA), 34W (700mA), 38W (800mA), 43W (900mA), 50W (1050mA) Suitable for installation on 3-circuit tracks, please check compatibility list on the instruction sheet. Compatible with OneTrack Electrical protection: Class I. Degree of protection: IP20, suitable for indoor environment only Light modules should be combined with suitable in-track drivers Nominal product dimensions: L.672mmx32mmx31mm

Atouts techniques

Dimensions (mm)



Photométrie

Pixo Line Driver Multipower 600 White

Code article 0007865

SYLVANIA

Données générales

Nom du produit	Pixo Line Driver Multipower 600 White
Technologie	Driver
Montage	Ceiling surface mounting
General application	Retail, Hospitality, Museums & Galleries, Office
Operating temperature range (°C)	-20°C...+40°C
ETIM Class	EC002710
Numéro virtuel FI	4279415
Warranty	5 ans

Données optiques

Couleur de lumière	N/A
Photobiological Risk Group	Not applicable

Caractéristiques électriques

Consommation électrique totale (W)	56
Primary Supply/Product voltage - min (V)	220.0
Primary Supply/Product voltage - max (V)	240.0
Lamp power factor	0.95
THD (at 230 V, 50 Hz, full load, at 100% dimming level) \leq xx.x %	10
Electrical protection	Class I
No. Of switching cycles before premature failures	>100000
Dimmable	Yes
Dimming method	Switch-dim (mains-rated)
Min. drive current (mA)	350
Max. drive current (mA)	1050
Drive current - Range (mA)	350mA / 1050mA
Courant d'appel (A)	42
Inrush Duration (μ s)	168
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. products per 10A C Breaker	15
Max. products per 16A C Breaker	24
Max. products per 10A B Breaker	9
Max. products per 16A B Breaker	14
Mains surge immunity (differential mode -> L-N) (kV)	1

Données physiques

Housing colour	White
IP rating	IP20
IK rating	IK03
Longueur (mm)	672
Largeur (mm)	31
Nominal Product Height (mm)	31.5
Poids (kg)	0.36

Pixo Line Driver Multipower 600 White

Code article 0007865

SYLVANIA

Emballage

Product EAN number	5410288078656
Longueur simple de l'emballage (cm)	68.0
Largeur simple de l'emballage (cm)	5.0
Packaging single depth (cm)	3.7
DUN14 (inner)	15410288078653
Units per outer package	20
Packaging outer length / height (cm)	70.0
Packaging outer width (cm)	27.0
Packaging outer depth (cm)	17.0

Sécurité

Glow Wire Test (°C)	650
Condition de fonctionnement optimal (° C)	-20-40