

ToLEDo T8 Universal V2 5FT 2800LM 840 RL

Code article 0029281


SYLVANIA



30,000 hours average rated life Last 1.5 times longer than standard fluorescent 58W T8 tri-phosphor lamp High switching cycles – 200,000X Up to 59% energy savings compared to the standard fluorescent lamp High lumen efficacy – up to 117lm/W Omni-directional light distribution and wide beam angle. Minimum and maximum operating temperature : -20°C to 50°C Glass construction and polycarbonate end-caps Must replace the fluorescent starter with LED dummy starter when used with magnetic/ CCG ballast Works only with compatible electronic ballasts. Please refer Sylvania website for full list of compatible ballast

Atouts techniques

Dimensions (mm)



Photométrie

ToLEDo T8 Universal V2 5FT 2800LM 840 RL

Code article 0029281

SYLVANIA

Données générales

| | |
|---|---|
| Nom du produit | ToLEDo T8 Universal V2 5FT 2800LM 840 RL |
| Technologie | LED |
| Puissance (nominale) (W) | 24 |
| Lamp shape | Tube, double-ended |
| Lamp finish | Opal |
| Fixture rating | Open |
| General application | Office, Hospitality, Retail, Logistics & Industry, Education, Residential & Consumer, Museums & Galleries |
| Operating temperature range (°C) | -20°C...+45°C |
| Performance ambient temperature Tq (°C) | 25 |
| Virtual assistant compatibility | N/A |
| ETIM Class | EC001959 |
| Numéro virtuel FI | 4941301 |
| Warranty | 3 ans |

Données optiques

| | |
|--|------------|
| Useful luminous flux (Φ_{use}) | 2800 |
| Flux lumineux utile (nominal) (lm) | 2800 |
| Température de couleur (K) | 4000 |
| Couleur de lumière | Cool White |
| IRC (Ra) | 80 |
| Colour Variation Initial (SDCM) | SDCM6 |
| Beam Angle (°) | 160 |
| Photobiological Risk Group | RG0 |
| Maintien du flux à la fin de la durée de vie nominale (lm) | 70 |

Caractéristiques électriques

| | |
|---|---------|
| Power consumption (W) | 24 |
| Wattage (W) | 24 |
| Primary Supply/Product voltage - min (V) | 220 |
| Primary Supply/Product voltage - max (V) | 240 |
| Lamp power factor | 0.9 |
| Control gear required | No |
| No. Of switching cycles before premature failures | >100000 |
| Dimmable | No |
| Courant d'appel (A) | 20.6 |
| Inrush Duration (μ s) | 45 |
| Lamp Energy Label (class) | E |
| Max. products per 16A C Breaker | 35 |
| Max. products per 16A B Breaker | 55 |

Durée de vie

| | |
|-------------------------------------|-------|
| Lifespan L70 B50 | 30000 |
| Average life (Nominal) (h) | 30000 |
| Durée de vie moyenne (nominale) (h) | 30000 |

Données physiques

| | |
|-------------------------------|------|
| IP rating | IP20 |
| Longueur (mm) | 1514 |
| Nominal Product Diameter (mm) | 28 |
| Poids (kg) | 0.2 |

ToLEDo T8 Universal V2 5FT 2800LM 840 RL

Code article 0029281

SYLVANIA

Emballage

| | |
|--------------------------------------|----------------|
| Product EAN number | 5410288292816 |
| Longueur simple de l'emballage (cm) | 151.0 |
| Largeur simple de l'emballage (cm) | 3.0 |
| Packaging single depth (cm) | 3.0 |
| DUN14 (inner) | 15410288292813 |
| Units per outer package | 10 |
| Packaging outer length / height (cm) | 150.7 |
| Packaging outer width (cm) | 21.0 |
| Packaging outer depth (cm) | 11.5 |

Sécurité

| | |
|---|---------------------------------------|
| Condition de fonctionnement optimal (° C) | -20-45 |
| Consignes de nettoyage en cas de bris | Not applicable |
| Lampe à objectif spécial | No |
| Ne convient pas à l'éclairage résidentiel | Yes |
| Safety message | Suitable for totally enclosed fixture |