

START Downlight 5in1 65-185 1750LM

Code article 0053149

SYLVANIA

Données générales

| | |
|----------------------------------|---|
| Nom du produit | START Downlight 5in1 65-185 1750LM |
| Technologie | LED |
| Cap/Base | N/A |
| Housing | PC Polycarbonate |
| Montage | Ceiling recessed mounting, Ceiling surface mounting |
| Built in presence detector | NONE |
| General application | Residential & Consumer |
| Operating temperature range (°C) | -20°C...+40°C |
| Virtual assistant compatibility | N/A |
| ETIM Class | EC001744 |
| Numéro virtuel FI | 4278427 |
| Warranty | 3 ans |

Données optiques

| | |
|---------------------------------|-----------|
| Fixture luminous flux (lm) | 1750 |
| Luminaire efficacy (lm/W) | 97 |
| Couleur de lumière | N/A |
| IRC (Ra) | 80 |
| Colour Variation Initial (SDCM) | SDCM6 |
| Beam Angle (°) | 110 |
| Distribution type | Symmetric |
| Glare control | < 28 |
| Photobiological Risk Group | RG0 |

Caractéristiques électriques

| | |
|--|-----------------------------|
| Consommation électrique totale (W) | 18 |
| Primary Supply/Product voltage - min (V) | 220.0 |
| Primary Supply/Product voltage - max (V) | 240.0 |
| Lamp power factor | 0.7 |
| THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x % | 85.0 |
| Electrical protection | Class II |
| Type d'appareillage | LED driver constant current |
| Dimmable | No |
| Dimming method | N/A |
| Drive current (mA) | 55 |
| Courant d'appel (A) | 2 |
| Inrush Duration (µs) | 100 |
| Energy Efficiency Class (A->G) of contained light source | E |
| Nominal Frequency (Hz) | 50/60Hz |
| LED Flickering Rate | Low (6% - 20%) |
| Max. products per 16A C Breaker | 62 |
| Max. products per 16A B Breaker | 34 |
| Connectable conductor cross section - Min (mm ²) | 0.75 |
| Connectable conductor cross section - Max (mm ²) | 1.5 |

Durée de vie

| | |
|------------------|-------|
| Lifespan L70 B50 | 55000 |
| Lifespan L80 B10 | 30000 |

START Downlight 5in1 65-185 1750LM

Code article 0053149

SYLVANIA

Données physiques

| | |
|-------------------------------|-------------------------|
| Housing colour | RAL 9003 - Signal white |
| IP rating | IP20 |
| IK rating | IK05 |
| Diffuser finish | Opal |
| Diffuser material | PC Polycarbonate |
| Finition réflecteur | Not Applicable |
| Nominal Product Height (mm) | 22 |
| Nominal Product Diameter (mm) | 217 |
| Poids (kg) | 0.413 |

Emballage

| | |
|--------------------------------------|----------------|
| Product EAN number | 5410288531496 |
| Longueur simple de l'emballage (cm) | 23.7 |
| Largeur simple de l'emballage (cm) | 4.3 |
| Packaging single depth (cm) | 22.7 |
| DUN14 (inner) | 15410288531493 |
| Units per outer package | 14 |
| Packaging outer length / height (cm) | 48.9 |
| Packaging outer width (cm) | 32.1 |
| Packaging outer depth (cm) | 25.2 |

Sécurité

| | |
|---|--------|
| Glow Wire Test (°C) | 650 |
| Condition de fonctionnement optimal (° C) | -20-40 |