

LSF PRO MULTI EXIT RC EM3 NM/MT DA BK

Code article 0038871

SYLVANIA

LiFeSafe




UK
CA



LiFeSafe PRO MULTI EXIT WR EM3 NM/MT DA is a black DALI addressable LED wall / wall recessed Exit sign. Maintained or Non-Maintained, 3Hr emergency duration. 4 ISO7010 Exit legends, Left, Right, Up and Down as an optional accessory included with the product. Maximum viewing distance 30m. 0 to +45°C operating temperature range. 140lm output (No legend kit fitted), IK03, IP65, Class II electrical construction, 6-year warranty.

Atouts techniques

Dimensions (mm)



Photométrie

LSF PRO MULTI EXIT RC EM3 NM/MT DA BK

Code article 0038871

SYLVANIA

Données générales

Nom du produit	LSF PRO MULTI EXIT RC EM3 NM/MT DA BK
Technologie	LED
Cap/Base	N/A
Housing	PC Polycarbonate
Montage	Wall recessed, Wall surface mounted
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office
Operating temperature range (°C)	0°C...+45°C
ETIM Class	EC001957
Warranty	6 years

Données optiques

Fixture luminous flux (lm)	50
Luminaire efficacy (lm/W)	10
Température de couleur (K)	5000
IRC (Ra)	70
Photobiological Risk Group	RG0
Maintien du flux à la fin de la durée de vie nominale (lm)	80
Luminous flux (emergency) (lm)	50
Flux lumineux (d'urgence) (lm)	50
Emergency duration (h)	3

Caractéristiques électriques

Lampe incluse	Fixture without Lightsource
Actuel (A)	0.017
Primary Supply/Product voltage - min (V)	220.0
Primary Supply/Product voltage - max (V)	240.0
Lamp power factor	0.35
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	82.3
Electrical protection	Class II
Control gear required	Yes
Type d'appareillage	LED driver constant current
Drive current (mA)	220
Courant d'appel (A)	30
Inrush Duration (µs)	220
Nominal Frequency (Hz)	50/60Hz
Max. products per 10A C Breaker	209
Max. products per 13A C Breaker	271
Max. products per 16A C Breaker	334
Max. products per 20A C Breaker	418
Max. products per 10A B Breaker	313
Max. products per 13A B Breaker	271
Max. products per 16A B Breaker	334
Max. products per 20A B Breaker	418
Connectable conductor cross section - Min (mm ²)	0.75
Connectable conductor cross section - Max (mm ²)	1.5
Durée de vie	
Lifespan L70 B10	120000
Lifespan L90 B10	100000

LSF PRO MULTI EXIT RC EM3 NM/MT DA BK

Code article 0038871

SYLVANIA

Données physiques

Housing colour	Black
IP rating	IP40
IK rating	IK03
Diffuser finish	Transparent
Diffuser material	PC Polycarbonate
Longueur (mm)	330
Largeur (mm)	190
Nominal Product Height (mm)	45
Poids (kg)	0.71
Recessed Depth (mm)	30

Emballage

Product EAN number	5410288388717
Longueur simple de l'emballage (cm)	33.0
Largeur simple de l'emballage (cm)	19.0
Packaging single depth (cm)	45.0
DUN14 (inner)	05410288388717
Units per outer package	1
Packaging outer length / height (cm)	33.0
Packaging outer width (cm)	19.0
Packaging outer depth (cm)	45.0

Sécurité

Glow Wire Test (°C)	850
Condition de fonctionnement optimal (° C)	0 °C-45
Utilisation pour applications sèches uniquement	Yes