

# ToLED<sub>o</sub> PLATINUM T8 CCG L1500 3250LM 865 100K RL

Code article 0030254


**SYLVANIA**



Energy efficient and affordable LED T8 solution to replace conventional fluorescent T8 lamps Omni-directional uniform light distribution thanks to glass tube construction design, same as traditional fluorescent T8 tubes High lumen package - 3330lm High lumen efficacy - 196 lm/W Switching cycles - 200,000X Average life 100,000 hours lifespan Lamp length - 1500mm Wide beam angle High power factor Suitable for general illumination in offices, supermarkets, department stores, train stations, petrol stations, parking lots and maintenance free applications Suitable for operation with magnetic ballast (CCG) and direct mains operation (AC 220-240V) 5-Year warranty

## Atouts techniques

### Dimensions (mm)



### Photométrie

# ToLED<sub>o</sub> PLATINUM T8 CCG L1500 3250LM 865 100K RL

Code article 0030254

**SYLVANIA**

## Données générales

Nom du produit	ToLED <sub>o</sub> PLATINUM T8 CCG L1500 3250LM 865 100K RL
Technologie	LED
Lamp shape	Tube, double-ended
Cap/Base	G13
Lamp finish	Frosted/Coated
General application	Hospitality, Logistics & Industry, Residential & Consumer, Retail
Operating temperature range (°C)	-20°C...+45°C
Virtual assistant compatibility	N/A
ETIM Class	EC001959
Numéro virtuel FI	4941369
Warranty	5 ans

## Données optiques

Useful luminous flux (Φ <sub>use</sub> )	3250
Température de couleur (K)	6500
Couleur de lumière	Daylight
IRC (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Beam Angle (°)	170
Photobiological Risk Group	RG0

## Caractéristiques électriques

Power consumption (W)	17
Wattage (W)	17
Actuel (A)	0.08
Primary Supply/Product voltage - min (V)	220.0
Primary Supply/Product voltage - max (V)	240.0
Lamp power factor	0.9
Control gear required	No
Dimmable	No
Courant d'appel (A)	3
Inrush Duration (µs)	100
Lamp Energy Label (class)	B
Nominal Frequency (Hz)	50/60Hz

## Durée de vie

Lifespan L70 B50	100000
------------------	--------

## Données physiques

IP rating	IP20
Longueur (mm)	1499
Nominal Product Diameter (mm)	28
Poids (kg)	0.22

## Emballage

Product EAN number	5410288302546
Longueur simple de l'emballage (cm)	155.0
Largeur simple de l'emballage (cm)	2.9
Packaging single depth (cm)	2.9
DUN14 (inner)	15410288302543
Units per outer package	10
Packaging outer length / height (cm)	161.0
Packaging outer width (cm)	22.0
Packaging outer depth (cm)	10.3

# ToLEDo PLATINUM T8 CCG L1500 3250LM 865 100K RL

Code article 0030254

**SYLVANIA**

## Sécurité

Condition de fonctionnement optimal (° C)	-20-45
Consignes de nettoyage en cas de bris	Not applicable
Lampe à objectif spécial	No
Ne convient pas à l'éclairage résidentiel	Yes
Safety message	Suitable for totally enclosed fixture