

SYLSMART HBIR29SV SSA

Code article 9041523

SYLVANIA



Wireless sensor for SylSmart Connected solution for Low Bay Applications

Atouts techniques

Photométrie

Données générales

Nom du produit	SYLSMART HBIR29SV SSA
Technologie	Sensor
Montage	Ceiling recessed mounting, Ceiling surface mounting
General application	Office
Operating temperature range (°C)	-20°C...+50°C
ETIM Class	EC000533
Warranty	5 ans

Caractéristiques électriques

Primary Supply/Product voltage - min (V)	220.0
Primary Supply/Product voltage - max (V)	240.0
Nominal Frequency (Hz)	50/60Hz

Données physiques

IP rating	IP20
Longueur (mm)	75.2
Nominal Product Diameter (mm)	78
Max. Lamp Length (mm) - C/L	75.2
Poids (kg)	0.094
Recessed Depth (mm)	71

Emballage

Product EAN number	4012289415235
Longueur simple de l'emballage (cm)	8.5
Largeur simple de l'emballage (cm)	8.5
Packaging single depth (cm)	9.5
Units per inner package	24
Packaging inner length / height (cm)	36.0
Packaging inner width (cm)	26.5
Packaging inner depth (cm)	23.5
Units per outer package	24
Packaging outer length / height (cm)	38.0
Packaging outer width (cm)	28.9
Packaging outer depth (cm)	27.1

SYLSMART HBIR29SV SSA

Code article 9041523



Sécurité

Condition de fonctionnement optimal (° C)	-20-50
---	--------