



FEATURES	
Technology	Basic
Energy Metering	No
Metering per Input Line	No
Metering per Output Receptacle	No
Remote Outlet Switching	No
Ethernet Port	No
Networking Protocols	No
PDU Cascading	No
Power Share	No
Display	No
Residual Current Monitoring	No
USB Ports	No
Environmental Sensors	No
INPUT	
Plug	T12 Plug
Lead Length	3 meter
Cable Type	H05VV-F3G1.0 mm <sup>2</sup>
Max. Input Load	10A
Rated Input Voltage	190-250V Single phase
Frequency	50-60Hz
Power Capacity	2300W
OUTPUT	
Rated Output Voltage	190-250V Single phase
Output Types	9 IEX (C13/C19) combo (Max rate 16A) EN61984+UL498 certified
Overload Protection	(1) Sang mao Thermal Fuse 10A
CHASSIS	
Dimensions (W x D x H)	483.6 x 44 x 44.4 mm
Color	Silver Anodize
Mounting Options	(2) 42 Bracket
Required Torque for Mounting Screws	≥2.54N·m (25.9kgf·cm or 22.4 in·lbs)
OPERATING ENVIRONMENT	
Temperature Range	0° to 60° C (30° to 140° F)
Humidity	0 - 95 %
Elevation	0 - 4000 Meters
CONFORMANCE	
IEC 62368-1 (Third Edition)	
   	