

INTERRATA ADJUSTABLE M IP67 CLEAR 1000LM 830 MB

Code article 0049042

SYLVANIA

Données générales

Nom du produit	INTERRATA ADJUSTABLE M IP67 CLEAR 1000LM 830 MB
Technologie	LED
Cap/Base	N/A
Housing	Aluminium
Montage	Ground recessed
General application	Hospitality, Museums & Galleries, Office, Residential & Consumer
Operating temperature range (°C)	-20°C...+40°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC000758
Numéro virtuel FI	4579505
Warranty	5 ans

Données optiques

Fixture luminous flux (lm)	1025
Luminaire efficacy (lm/W)	76
Température de couleur (K)	3000
Colour Code	830
Couleur de lumière	Warm White
IRC (Ra)	80
Colour Variation Initial (SDCM)	SDCM5
Beam Angle (°)	30
Distribution type	Symmetric
Photobiological Risk Group	RG1

Caractéristiques électriques

Consommation électrique totale (W)	13.5
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240
Electrical protection	Class I
Dimmable	No
Drive current (mA)	600
Courant d'appel (A)	15
Inrush Duration (µs)	200
Energy Efficiency Class (A->G) of contained light source	F
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Low (6% - 20%)
Max. products per 10A C Breaker	50
Max. products per 13A C Breaker	65
Max. products per 16A C Breaker	80
Max. products per 20A C Breaker	100
Max. products per 10A B Breaker	30
Max. products per 13A B Breaker	39
Max. products per 16A B Breaker	48
Max. products per 20A B Breaker	60

Durée de vie

Lifespan L70 B50	50000
------------------	-------

Données physiques

Housing colour	Stainless steel
IP rating	IP67
IK rating	IK10
Diffuser material	Glass
Nominal Product Height (mm)	229
Nominal Product Diameter (mm)	200
Poids (kg)	2.3

INTERRATA ADJUSTABLE M IP67 CLEAR 1000LM 830 MB

Code article 0049042

SYLVANIA

Emballage

Product EAN number	5410288490427
Longueur simple de l'emballage (cm)	21.0
Largeur simple de l'emballage (cm)	21.0
Packaging single depth (cm)	24.0
DUN14 (inner)	15410288490424
Units per outer package	4
Packaging outer length / height (cm)	44.0
Packaging outer width (cm)	44.0
Packaging outer depth (cm)	25.5

Sécurité

Condition de fonctionnement optimal (° C)	-20-40
---	--------