

Concord

Raiden IP66 3KLM 840 Street 2824059



Features

- Outdoor and indoor floodlight range with in house design, comes complete with 1m flying lead and adjustable bracket, aluminium housing, RAL 9022 - Pearl light grey, clear glass diffuser, IP66, IK08, Class I, 4000K, Non-dimming, 3050lm, 26W, 117lm/W, CRI80, Street beam angle 155*75°, 100000 hrs L80B50 lifespan, 254x203x68mm (LxWxH) dimensions, 2.1kg weight.


Product Overview

Product name	Raiden IP66 3KLM 840 Street
Technology	LED
Cap/Base	N/A
Housing	Aluminium
General application	Logistics & Industry
ETIM Class	EC001744
Fixture luminous flux (lm)	3050
Luminaire efficacy (lm/W)	117
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Beam Angle (°)	Not Applicable
Beam Angle (°)	155*75
Photobiological Risk Group	RG1
Total power consumption (W)	26
Electrical protection	Class I
Dimmable	No
Housing colour	RAL 9022 - Pearl light grey
IP rating	IP66
IK rating	IK08
Product EAN number	5025768240593
Warranty	5 years


Concord

Raiden IP66 3KLM 840 Street
2824059

Photometry



Technical drawings



Data table

GENERAL DATA

Product name	Raiden IP66 3KLM 840 Street
--------------	-----------------------------

Concord

Raiden IP66 3KLM 840 Street
2824059

Technology	LED
Cap/Base	N/A
Housing	Aluminium
General application	Logistics & Industry
Operating temperature range (°C)	-40°C - 50°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001744
Warranty	5 years

OPTICAL DATA

Fixture luminous flux (lm)	3050
Luminaire efficacy (lm/W)	117
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Beam Angle (°)	Not Applicable
Beam Angle (°)	155*75
Photobiological Risk Group	RG1

ELECTRICAL DATA

Total power consumption (W)	26
Mains voltage (V)	220-240V~
Lamp power factor	0.95
Electrical protection	Class I
Control gear required	No
Transformer required	No
Dimmable	No
Drive current (mA)	510
Inrush Current (A)	45
Inrush Duration (µs)	110
Glow Wire Test (°C)	850
Nominal Frequency (Hz)	50/60Hz

Concord

Raiden IP66 3KLM 840 Street
2824059

Max. Luminaires per 10A C Breaker	22
Max. Luminaires per 13A C Breaker	28
Max. Luminaires per 16A C Breaker	36
Max. Luminaires per 20A C Breaker	36
Max. Luminaires per 10A B Breaker	17
Max. Luminaires per 13A B Breaker	22
Max. Luminaires per 16A B Breaker	27
Max. Luminaires per 20A B Breaker	34

LIFETIME DATA

Lifespan L70 B50	100000
Lifespan L80 B20	100000

PHYSICAL DATA

Housing colour	RAL 9022 - Pearl light grey
IP rating	IP66
IK rating	IK08
Nominal Product Length (mm)	254
Nominal Product Width (mm)	203
Nominal Product Height (mm)	68
Nominal Product Diameter (mm)	Not applicable
Weight (kg)	2.1

PACKAGING

Single packaging type	Carton
Product EAN number	5025768240593
Packaging single length / height (cm)	30.5
Packaging single width (cm)	20.9
Packaging single depth (cm)	12.0
DUN14 (outer)	15025768240590
Units per outer package	5
Packaging outer length / height (cm)	62.5
Packaging outer width (cm)	32.0
Packaging outer depth (cm)	32.0

Concord

Raiden IP66 3KLM 840 Street
2824059

SAFETY DATA

Optimal operating condition (°C)	-40-50
Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No